RECLANIATION Managing Water in the West

Modeling in the Deschutes Basin

Jennifer Johnson, P.E., Bureau of Reclamation



U.S. Department of the Interior Bureau of Reclamation


Outline

- Review of Models
- Climate Modeling Process



Models


- Hydrologic
 - VIC, PRMS
- Groundwater
 - MODFLOW (2004, current)
- Combined
 - GSFlow
- Water Resources
 - MODSIM, RiverWare



Hydrologic Models

VIC


- Takes temperature and precipitation as input
- Simulates rainfall-runoff process
- Generates flow at each cell which is then routed to specific points
- Does not simulate deep groundwater flow



Hydrologic Models


PRMS

- Takes temperature and precipitation as input
- Simulates rainfall-runoff process
- Generates routed flows at specified points




Groundwater

- MODFLOW
 - USGS updated their MODFLOW model of the basin
 - Refined grid allowing for better stream definition
 - Refined layering




Coupled


- GSFlow
 - Combines PRMS with MODFLOW
 - Better representation of streamflows that are highly influenced by groundwater
 - Takes inputs of temperature and precipitation
 - Generates flow at specified points





Water Resources

- MODSIM and RiverWare
 - MODSIM monthly timestep
 - RiverWare daily timestep
- Networks are similar
 - Upper Deschutes, Crooked River, Whychus Creek
- Both simulate
 - Reservoir operations
 - Irrigation diversions
 - Flow in the river
 - Groundwater return flows
 - Water rights













 1. Generate future projected temperature and precipitation.







- 1. Generate future projected temperature and precipitation.
 - Decisions:
 - CMIP3 vs CMIP5
 - Extreme or Moderate Risk
 - 10/50/90 or 20/50/80
 - Future time periods
 - Investigate the change between recent history and 2020s, 2040s, 2060s, 2080s
 - Number of climate scenarios
 - 3 or 5





- 2. Generate future projected stream flows
 - Decisions:
 - VIC or GSFlow
 - VIC recommended for Crooked
 - GSFlow recommended for Upper Deschutes
 - » GSFlow dependent on USGS schedule
- 3. Simulate impacts to groundwater
 - Primary impacts
 - Changes in recharge
 - Secondary impacts
 - Changes in behavior





- 4. Run generated flows through water resources model
 - Decisions
 - MODSIM or RiverWare
 - Irrigation demands
 - Pattern of historic diversions?
 - Adjusted for future ET?
 - Adjusted for future land use and crop type?
 - Metrics
 - Probability of reservoir fill
 - Irrigation shortages
 - Probability of meeting flow targets
 - Number of scenarios is multiplied by climate scenarios

Questions



Presenter:

Jennifer Johnson | Civil Engineer (Hydrologic) | Pacific Northwest Regional Office – River & Reservoir Operations (208) 378-5225 | jmjohnson@usbr.gov